

COMPANY IDENTITY: CSD/Startex
PRODUCT IDENTITY: PAINT & VARNISH REMOVER

DATE: 05/03/10
PAGE: 1 OF 7

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.
THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)
IMPORTANT: Read this SDS before handling & disposing of this product.
Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: PAINT & VARNISH REMOVER
NEW MSDS DATE: 05/03/2010
COMPANY IDENTITY: CSD/Startex
COMPANY ADDRESS: P O Box 3087
COMPANY CITY: Conroe, TX 77305
COMPANY PHONE: 1-936-228-0865
EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA)

SECTION 2. HAZARDS IDENTIFICATION

DANGER!!

EXPOSURE PREVENTION: STRICT HYGIENE!
AVOID EXPOSURE OF (PREGNANT) WOMEN, ADOLESCENTS, CHILDREN!

RISK STATEMENTS:

R12/13 Extremely Flammable! Serious electrostatic hazard!
R36/37/38 Irritating to eyes, respiratory system and skin.
R39/23/24/25 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R20/65 Harmful by inhalation, may cause lung damage if swallowed.
R41 Risk of serious damage to eyes.
R63 Possible risk of harm to the unborn child.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapors may cause drowsiness and dizziness.

SAFETY STATEMENTS:

S7/9 Keep container tightly closed and in a well-ventilated place.
S36/37 Wear suitable protective clothing and gloves.
S16 Keep away from sources of ignition. No smoking.
S24 Avoid contact with skin.
S45 In case of accident, or if you feel unwell, seek medical advice immediately. (Show the label where possible).
S46 If swallowed, seek medical advice immediately, and show this container or label.

SEE SECTION 11 FOR OTHER TOXICOLOGICAL INFORMATION (ACUTE & CHRONIC HAZARDS)

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT%	TWA (OSHA)	TLV (ACGIH)
Toluene	108-88-3	203-625-9	45-55	200 ppm	50 ppm A4
Acetone	67-64-1	200-662-2	15-25	1000 ppm	500 ppm A4
Methanol	67-56-1	200-659-6	15-25	200 ppm S	200 ppm S
Paraffin Wax	(Mixture)	-	0- 5	None Known	None Known
KULCEL H	(Mixture)	-	0- 5	None Known	None Known

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS (CONTINUED)

MATERIAL	CAS#	EINECS#	CEILING	STEL(OSHA/ACGIH)	HAP
Toluene	108-88-3	203-625-9	None Known	None Known	Yes
Acetone	67-64-1	200-662-2	None Known	750 ppm	No
Methanol	67-56-1	200-659-6	None Known	250 ppm	Yes

In addition to EPA Hazardous Air Pollutants showing `Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Mixed Xylenes, Ethylbenzene

SECTION 4. FIRST AID MEASURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING:

Induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. If no medical personnel are available & patient is conscious, ingestion of an alcoholic beverage may prevent blindness, death. Do NOT induce vomiting to an unconscious or convulsing person.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES

NO open flames, NO sparks, & NO smoking. Use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

EXTINGUISHING MEDIA

Use dry powder, AFFF, alcohol-resistant foam, water in large amounts, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE
Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE MEASURES:

EVACUATE DANGER AREA! Consult an expert!
Vapors may ignite explosively & spread long distances. Prevent vapor buildup.
Keep unprotected personnel away. Ventilate spill area. Remove all ignition sources.
Use complete chemical protective suit with self-contained breathing apparatus.

ENVIRONMENTAL PRECAUTIONS:

Do NOT let this chemical enter the environment.
Keep from entering storm sewers and ditches which lead to waterways.

CONTAINMENT AND CLEAN-UP MEASURES:

Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers.
Absorb remaining liquid in sand or inert absorbent. Remove to safe place.

SECTION 7. HANDLING AND STORAGE

HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
Avoid contact with skin & eyes.
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!
To minimize static discharge when transferring, ensure electrical continuity by bonding and grounding all equipment. Use an inlet line diameter of at least 3.5 inches (8.9 centimeters) with a maximum flow rate of 1 meter/second.

STORAGE

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.
Keep in fireproof surroundings. Keep separated from strong oxidants, food & feedstuffs. Keep cool. Do not store above 49 C/120 F.
Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION

LOCAL EXHAUST:	Necessary	MECHANICAL (GENERAL):	Acceptable
SPECIAL:	None	OTHER:	None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers.
Wash at end of each workshift & before eating, smoking or using the toilet.
Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Liquid, Water-White
ODOR:	Ketone
ODOR THRESHOLD:	Not Available
pH (Neutrality):	Not Applicable
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP, 50%, Dry Point):	56 83 111*C/133 182 232*F(*=End Point)
FLASH POINT (TEST METHOD):	-16 C / 2 F (TCC) (Lowest Component)
EVAPORATION RATE (n-BUTYL ACETATE=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Class I B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	3.0
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	91.4
VAPOR DENSITY (air=1):	2.0
GRAVITY @ 68/68 F / 20/20 C:	
SPECIFIC GRAVITY (Water=1):	0.835
POUNDS/GALLON:	6.958
WATER SOLUBILITY:	Appreciable
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	463 C / 867 F
DECOMPOSITION TEMPERATURE:	Not Available
REFRACTIVE INDEX:	1.423
MIXED ANILINE POINT (Acid Insol):	10 C / 50 F
VOC'S (>0.44 Lbs/Sq In) :	95.3 Vol% / 796.3 g/L / 6.6 Lbs/Gal
TOTAL VOC'S (TVOC):	95.6 Vol% / 796.3 g/L / 6.6 Lbs/Gal
NONEXEMPT VOC'S (CVOC):	72.9 Vol% / 616.5 g/L / 5.1 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	74.0 Wt% / 616.5 g/L / 5.1 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	48.6

SECTION 10. STABILITY & REACTIVITY

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

Reacts violently with strong oxidants, causing fire & explosion hazard.
Attacks many plastics, coatings.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.
Absorption thru skin increases exposure.
Primary irritation to eyes, redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation.
Acute overexposure can cause harm to kidneys, blood, nerves, liver, lungs.
Repeated exposure over TLV can cause blindness.
Use of alcoholic beverages enhances the harmful effect.

SWALLOWING:

Can be fatal or cause blindness if swallowed. Cannot be made non-poisonous.
POISON ! Can cause irreversible nervous system damage & death.
Harmful or fatal if swallowed.
Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.
The symptoms of chemical pneumonitis may not show up for a few days.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to kidneys, blood, nerves, liver, lungs.
Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Pregnant women should avoid use. May cause birth defects.
Leukemia been reported in humans from Benzene.
This product contains less than 157 ppm of Benzene.
Not considered hazardous in such low concentrations.
Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.
Depending on degree of exposure, periodic medical examination is indicated.

MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Methanol	67-56-1	200-659-6	LOWEST KNOWN LD50 (ORAL) 1000.0 mg/kg (Man)
Toluene	108-88-3	203-625-9	LOWEST KNOWN LC50 (VAPORS) 5300 ppm (Mice)
Toluene	108-88-3	203-625-9	LOWEST KNOWN LD50 (SKIN) 4000.0 mg/kg (Rabbits)

COMPANY IDENTITY: CSD/Startex
PRODUCT IDENTITY: PAINT & VARNISH REMOVER

DATE: 05/03/10
PAGE: 6 OF 7

SECTION 12. ECOLOGICAL INFORMATION

AQUATIC ANIMAL INFORMATION:

The most sensitive known aquatic group to any component of this product is:
Goldfish 250 ppm or mg/L (24 hour exposure).
Keep out of sewers and natural water supplies.
The substance is toxic to aquatic organisms.

MOBILITY IN SOIL

This material is a mobile liquid.

DEGRADABILITY

This product is partially biodegradable.

ACCUMULATION

Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste management options.
Recycle / dispose of observing national, regional, state, provincial and local
health, safety & pollution laws. If in doubt, contact appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

DOT SHIPPING NAME: UN1263, Paint Related Material, 3, PG-II
DRUM LABEL: (FLAMMABLE LIQUID)
IATA / ICAO: UN1992, Flammable Liquids, Toxic, n.o.s.
(Contains: Toluene, Acetone, Methanol), 3, PG-II
IMO / IMDG: UN1992, Flammable Liquids, Toxic, n.o.s.
(Contains: Toluene, Acetone, Methanol), 3, PG-II
EMERGENCY RESPONSE GUIDEBOOK NUMBER: 131

If container has greater than the RQ of products (SEE SECTION 15), put ",RQ,"
after UN# of DOT Shipping Name. List the products which are greater than RQ.

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the
reporting requirements of Section 313 of the Emergency Planning & Community
Right-To-Know Act of 1986 & of 40 CFR 372. This information must be
included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS

	CAS#	EINECS#	WT%	(REG.SECTION)	RQ(LBS)
*Toluene	108-88-3	203-625-9	45-55	(311,312,313,RCRA)	1000
Acetone	67-64-1	200-662-2	15-25	(311,312)	5000
*Methanol	67-56-1	200-659-6	15-25	(311,312,313,RCRA)	5000

COMPANY IDENTITY: CSD/Startex
PRODUCT IDENTITY: PAINT & VARNISH REMOVER

DATE: 05/03/10
PAGE: 7 OF 7

SECTION 15. REGULATORY INFORMATION (CONTINUED)

> 1907 LB / 866 KG OF THIS PRODUCT IN 1 CONTAINER EXCEEDS THE "RQ" OF TOLUENE.
Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively.
Failure to report may result in substantial civil and criminal penalties.
State & local regulations may be more restrictive than federal regulations.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: This product contains the following chemical known to the State of California to cause reproductive toxicity: Toluene

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:
Australia, Canada, China, Europe (EINECS), Japan, Korea, United Kingdom.

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B2: Flammable Liquid.
D2B: Irritating to skin / eyes.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 3, FLAMMABILITY: 3, REACTIVITY: 0
(Personal Protection Rating to be supplied by user based on use conditions.)
This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.
Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.
This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.